

QY25E-1

LOAD CHARTS

319171111111

Table 3-3 Rated lifting capacity table (with the 5th outrigger)

Unit : kg

幅度 Radius (m)	主 臂 Boom (m)					主臂 仰角 boom angle	主臂 + 副臂 Boom + Jib 32 + 7.5 (m)					
	支腿全伸 Outrigger fully extended.		全方位作业 full direction working area				副臂安装角 0° jib offset		副臂安装角 15° jib offset		副臂安装角 30° jib offset	
	10.2	15.65	21.1	26.55	32.0		侧后方 Side	前方 front	侧后方 side, rear	前方 front	侧后方 side, rear	前方 front
3.0	25000					80	3000	3000	2400	2400	1500	1500
3.5	25000	14600				78	3000	3000	2300	2400	1500	1500
4.0	24000	14600	10000			76	2950	2950	2200	2200	1450	1450
4.5	22000	14600	10000	8000		74	2800	2800	2100	2100	1400	1400
5.0	19000	14600	10000	8000		72	2700	2700	2050	2050	1350	1350
5.5	17000	14000	10000	8000	6500	70	2550	2500	2000	2000	1300	1300
6.0	15500	13500	10000	8000	6500	68	2450	2200	1900	1900	1250	1250
7.0	12000	12200	9000	8000	6500	66	2350	1900	1800	1700	1230	1230
8.0	9500	9700	8000	7500	6000	64	2200	1600	1750	1500	1200	1200
9.0	7500	7800	7500	7000	5500	62	2100	1400	1650	1250	1180	1180
10.0		6500	6500	6000	5000	60	2000	1200	1600	1100	1150	1000
11.0		5500	5800	5500	4700	58	1800	1000	1550	900	1130	850
12.0		4600	4500	5000	4300	56	1600	800	1450	750	1110	700
13.0		4000	4000	4250	4000	54	1450	700	1400	650	1080	600
14.0			3500	3750	3700	52	1300	550	1250	550	1050	500
15.0			3000	3250	3500	50	1200	450	1100	400	1030	400
16.0			2500	2900	3000	45	900	250	850	200	800	200
18.0			2000	2400	2500	40	650		650		600	
20.0				1900	1900	35	500		500		450	
22.0				1500	1500	30	350		350		300	
24.0					1200							
26.0					900							
28.0					700							
30.0					550							